

Traps



Moisture

The 580 1800 Series traps are designed for use in high purity gas systems to prevent the possible introduction of moisture into the instrumentation carrier gases. The trap has a maximum flow rate of 70 LPM air at 100 PSIG.



Hydrocarbon

The 580 1900 Series hydrocarbon traps are designed to remove organic compounds from carrier gases, air and hydrogen. These high capacity traps contain 200cc of carbon impregnated filter media. Excellent efficiencies are achieved for the removal of the following; Acetone, any Acetate dissolved in oil, Isopropyl Alcohol, Mercaptans and organic acids, as some examples.



Oxygen

The 580 1600 Series oxygen traps contain highly active, metal containing inert reagents capable of reducing the oxygen content in a gas stream to less than 15 ppb. These traps can remove up to 2 grams of moisture with no effect on oxygen capacity. Typical applications involve, but are not exclusive to, Nitrogen, Helium, Argon, Carbon Dioxide, and low boiling point aromatics such as Benzene, Toluene and Alkyl Benzene's for oxygen cleaner gases.



Indicating O₂

The 580 1600 Series indicating oxygen traps contain highly active, metal containing inert reagents capable of reducing the oxygen content in a gas stream to less than 2 ppb. As the metal is oxidized, it changes color indicating the presence of Oxygen. Typical applications involve, but are not exclusive to, Nitrogen, Helium, Argon, Carbon Dioxide, and low boiling point aromatics such as Benzene, Toluene and Alkyl Benzene's for oxygen cleaner gases.

Materials and Specifications

| | |
|-------------------------------|----------------------|
| Tube | Polycarbonate |
| Seals | Buna-N |
| Filters | 316L Stainless steel |
| Max Operating Pressure | 125 PSIG (8.62 BAR) |

Materials and Specifications

| | |
|-------------------------------|----------------------|
| Tube | Polycarbonate |
| Seals | Buna-N |
| Filters | 316L Stainless steel |
| Max Operating Pressure | 125 PSIG (8.62 BAR) |

Materials and Specifications

| | |
|-------------------------------|----------------------|
| Tube | Aluminum |
| Seals | Buna-N |
| Filters | 316L Stainless steel |
| Max Operating Pressure | 125 PSIG (8.62 BAR) |

Materials and Specifications

| | |
|-------------------------------|----------------------|
| Tube | Glass |
| Seals | Buna-N |
| Filters | 316L Stainless steel |
| Max Operating Pressure | 100 PSIG (7 BAR) |

Ordering Information

| Moisture Traps | End Fittings | Removal Capacity (H ₂ O) | Catalyst |
|-------------------------|--------------------------|---|------------------|
| 580 1805 | 1/8" Brass tube fitting | 36.0 grams (H ₂ O < 18 ppb) | 13X mole sieve |
| 580 1806 | 1/4" Brass tube fitting | 36.0 grams (H ₂ O < 18 ppb) | 13X mole sieve |
| 580 1807 | 1/8" Brass tube fitting | 72.0 grams (H ₂ O < 14 ppb) | 13X mole sieve |
| 580 1808 | 1/4" Brass tube fitting | 72.0 grams (H ₂ O < 14 ppb) | 13X mole sieve |
| 580 1800 | Refill (1) 580 1807/1808 | N/A | 13X mole sieve |
| Hydrocarbon Traps | End Fittings | Removal Capacity (C ₄) | Catalyst |
| 580 1903 | 1/8" Brass tube fitting | 30 grams (C ₄ Hydrocarbons < 15 ppb) | Activated carbon |
| 580 1904 | 1/4" Brass tube fitting | 30 grams (C ₄ Hydrocarbons < 15 ppb) | Activated carbon |
| 580 1900 | Refill (2) 580 1903/1904 | N/A | Activated carbon |
| Oxygen Traps | End Fittings | Removal Capacity (O ₂) | Catalyst |
| 580 1602 | 1/8" Brass tube fitting | 600 mg (O ₂ < 15 ppb) | Activated metal |
| 580 1604 | 1/4" Brass tube fitting | 600 mg (O ₂ < 15 ppb) | Activated metal |
| Indicating Oxygen Traps | End Fittings | Removal Capacity (O ₂) | Catalyst |
| 580 1608 | 1/8" Brass tube fitting | 30 mg (O ₂ < 2 ppb) | Activated metal |
| 580 1609 | 1/4" Brass tube fitting | 30 mg (O ₂ < 2 ppb) | Activated metal |