



9900 Series Pipeline Regulator

Heavy Duty Heating and Cutting at Point of Use

Features

- Rear entry
 - *Excellent visibility*
- Flat seat design
 - *Instant high flow*
- Soft seat material
 - *Minimal pressure drop*

Material

- Brass barstock body
- Neoprene® seat
- 55-micron sintered capsule filter

Specification

- 450 PSIG max inlet
- Cv = .45



8069945 Shown

Series	Part Number	Gas Service	Delivery	Gauge	Inlet	Outlet
9900	8069940	Oxygen	0-200 PSIG	0-400 PSIG	CGA 024 RH	'B' 9/16"-18 (RH Ext.)
	8069941	Oxygen	0-40 PSIG	0-60 PSIG	CGA 024 RH	'B' 9/16"-18 (RH Ext.)
	8069943	Fuel Gases (Acetylene, Propane, Natural Gas)	0-15 PSIG	0-30 PSIG	CGA 025 LH	'B' 9/16"-18 (LH Ext.)
	8069944	General	0-40 PSIG	0-60 PSIG	1/4" FNPT	1/4" FNPT
	8069945	Inerts (Nitrogen, Helium, Argon)	0-200 PSIG	0-400 PSIG	CGA 034 RH	'B' 5/8"-18 (RH Ext.)
	8069949	Fuel Gases (Not for Acetylene)	0-40 PSIG	0-60 PSIG	CGA 025 LH	'B' 9/16"-18 (LH Ext.)

* Not included.

Note: Acetylene should not be used over 15 PSIG